Steel Floor Lock 5-5/8 to 6-1/4 In. Height Silver

MODEL FL-LKL-5

Facilities Maintenance / Polyurethane Floor Locks



PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to created a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

CORE PRODUCT DATA

ASSEMBLED WEIGHT **2 lbs**	ASSEMBLED SIZE **3.875" W x 4.4375" L x 5.625" H**	SHIP WEIGHT **2 lbs**
PACKAGE 1 SIZE **6" W x 5" D x 6" H**	COLOR / FINISH **Silver**	FREIGHT TYPE **Parcel**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS






PRODUCT SPECIFICATIONS

Lowered Height (in.)	5-5/8
Raised Height (in.)	6-1/4
Foot Pad Diameter (in.)	2-9/16
Foot Pad Material	Thermoplastic polyurethane (TPU)
Mounting Plate (in.)	3-7/8 x 3-9/16
Slotted Holes on Center (in.)	1-3/4 x 3-1/16
Mounting Plate Thickness (in.)	5/16
Slotted Mounting Hole Width/Height (in.)	3/8 x 1/2
Inside Bolt Hole Spacing (in.)	2-13/16 X 1-3/4
Outside Bolt Hole Spacing (in.)	3-1/16 X 1-3/4
Suggested Caster Size (in.)	5

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **30 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?FID=1067