

# Aluminum Portable Work Area Gantry Crane 47-3/4"L x 120"W x 91-13/16"H Beam 2,000 Lb. Capacity Silver

**MODEL FPG-A-20-10**

Overhead Lifting / Aluminum Work Area Portable Gantry Cranes

## PRODUCT OVERVIEW

Built to dependably make the workplace a safer environment, this gantry crane minimizes the manual handling needed for large, oversized material. The unchangeable height and width dimensions of the unit, provides a level of consistency needed when contending with heavy objects. With a portable design, the crane can simply be wheeled to a new location without the need for the unit to be deconstructed. This crane is not to be moved when loaded.

## KEY FEATURES

- Non-adjustable, fixed height design
- Rust resistant aluminum construction
- 5" poly on steel casters
- To be used on flat surfaces only

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**177 lbs**

**ASSEMBLED SIZE**  
**120" W x 47.75" L x 91.8125" H**

**SHIP WEIGHT**  
**212 lbs**

**PACKAGE 1 SIZE**  
**29" W x 120" D x 15" H**

**COLOR / FINISH**  
**Silver**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                   |
|--------------------------------------|-------------------|
| Uniform Capacity (lb.)               | 2,000             |
| Under I-Beam to Ground Length (in.)  | 85-13/16          |
| Between Upright Width (in.)          | 101-3/8           |
| Overall I-Beam Length (in.)          | 120               |
| Usable I-Beam Length (in.)           | 96-1/4            |
| Overall Width (in.)                  | 47-3/4            |
| Overall Height (In.)                 | 91-13/16          |
| Caster Quantity/Diameter/Width (in.) | (4) 5x2           |
| Caster Material                      | Poly-on-Steel     |
| Caster Type                          | Swivel with Brake |
| Usable Height (in.)                  | 85-13/16          |
| I-Beam Height (in.)                  | 6                 |
| Flange Width (in.)                   | 3-5/16            |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1784>