

Steel Heavy Duty Low Profile Self Dumping Hopper 2 Cubic Yard 6000 Lb. Capacity Blue

MODEL H-200-HD

Fork Truck Attachments / H Style - Low Profile 90 degrees Self-Dumping Steel Hoppers

PRODUCT OVERVIEW

The Heavy Duty Low Profile 90 degree self-dumping steel Hopper feature a full ninety (90) degree dump angle with a cushioned rubber bumper stop. The low profile design is essential for convenient loading. Dumping with a fork truck is quick and simple. A cable is pulled from the seat of the fork truck to dump the hopper. The unit returns to an upright and locked position when lowered to the ground. Fork pockets are 22" long and are capped on the end to allow for 90 degrees dump. The included safety restraint/chain must be securely attached to the lift truck carriage without slack. Models with same overall width may be stacked. For example, models H-25 may be stacked with H-50's, the H-100's can be stacked with H-150's, while the H-200 hoppers can o...

KEY FEATURES

- Low-profile design makes loading easier
- Included manual pull-cable dumps hopper from seat of fork truck
- Full 90 degrees dump angle returns to upright position when lowered to ground
- Features heavy-duty latch mechanism for worker safety

CORE PRODUCT DATA

ASSEMBLED WEIGHT
574 lbs

ASSEMBLED SIZE
67" W x 56.5625" L x 38.6875" H

SHIP WEIGHT
575 lbs

PACKAGE 1 SIZE
64" W x 70" D x 43" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	6,000
Steel (gauge)	8
Volume (cu. yrd.)	2
Fork Pocket Center (in.)	21-5/8
Usable Fork Pocket Length (in.)	21-7/8
Usable Fork Pocket Width (in.)	7
Usable Fork Pocket Height (in.)	2
Front Lip to Floor (in.)	26-15/16
Formed Base Thickness (in.)	1/4
Pull Cable Length (ft.)	4
Overall Width (in.)	67
Overall Length (in.)	56-9/16
Overall Height (in.)	38-11/16

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=445>