# Steel Hydraulic Beam Trailer Stabilizing Jack 100,000 Lb. Static Capacity Yellow

**MODEL H-LO-J-BEAM**

Loading Dock Equipment / Trailer Stabilizing Jacks



## PRODUCT OVERVIEW

Trailer stabilizing jacks are used to prevent up-ending of semi-trailers when they are not connected to a tractor during loading and unloading operations. Throughout the loading and unloading process it is always recommended to use two jacks, one on each side of the front of the trailer. The trailer must be situated on a flat, stable and improved (preferably concrete) surface, while the jack sits perpendicular to the underside of the trailer. Every jack is built of a high strength steel construction with a flush-type Zerk fitting for lubricating ACME screw. A yellow powder coat finish and a reflective collar for visibility at night are both included. Each jack meets OSHA regulations when used with wheel chocks. **The color of handles included with...

## KEY FEATURES

- Rectangle top plate
- Reflective collar increases visibility at night
- Manual raising and lowering mechanism
- Meets OSHA regulations when used with wheel chocks

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**168 lbs** | ASSEMBLED SIZE<br>**23.75" W x 26.6875" L x 47" H** | SHIP WEIGHT<br>**158 lbs** |
| PACKAGE 1 SIZE<br>**40" W x 48" D x 45" H** | COLOR / FINISH<br>**Yellow** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS






## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Static Capacity (lb.)** | 100,000 |
| **Uniform Lifting Capacity (lb.)** | 40,000 |
| **Lowered Height (in.)** | 41 |
| **Raised Height (in.)** | 47 |
| **Wheel Quantity/Diameter/Width (in.)** | (2) 10 x 2 |
| **Wheel Type** | Hard Rubber |
| **Front Wheel Quantity/Diameter/Width (in.)** | (1) 4 x 1-1/4 |
| **Front Wheel Type** | Steel |
| **Jack Type** | Hydraulic |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=90