

# Steel Portable Hydraulic Drum Dumper 60 In. Dump Height 750 Lb. Capacity Blue / Yellow

**MODEL HDD-60-7-P**

Drum Handling Equipment / Hydraulic Drum Dumpers

## PRODUCT OVERVIEW

The Hydraulic drum dumper is what you need to dump heavy drums. Works with plastic, steel, and fiber drums. Dumper has a solid steel chute. this portable unit has casters with floor lock screws. All steel construction. Upper travel limit switch, emergency brass safety velocity fuse in cylinder, and vertical adjustment drum restraints are standard. Dumper is operated with a hand held control on a coil cord standard.

## KEY FEATURES

- Internal pre-wired heavy-duty electric motor conveniently dumps drums
- Adjustable drum restraints work with all types of 30 and 55 gallon drums
- Drum rotation design may be stopped at any point
- Solid steel construction offers long lasting reliable use

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**887 lbs**

**ASSEMBLED SIZE**  
**36" W x 80" L x 84.5" H**

**SHIP WEIGHT**  
**998 lbs**

**PACKAGE 1 SIZE**  
**44" W x 96" D x 91" H**

**COLOR / FINISH**  
**Blue (Frame), Yellow (Chute)**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                             |                        |
|---------------------------------------------|------------------------|
| Uniform Capacity (lb.)                      | 750                    |
| Dump Height (in.)                           | 60                     |
| Rotated Height (in.)                        | 136-3/4                |
| Level Height (in.)                          | 84                     |
| Accepts                                     | 30 and 55-gallon drums |
| Motor Horsepower                            | 3/4                    |
| Single Phase (volts)                        | 115                    |
| Motor (Hz)                                  | 60                     |
| Power Cord Length (ft.)                     | 8                      |
| Hand Held Control Cord Length (in.)         | 18-90                  |
| Drum Rotation (deg.)                        | 135                    |
| Dump Angle (deg.)                           | 45                     |
| Chute Diameter (in.)                        | 24                     |
| Raise Time (sec.)                           | 42                     |
| Motor Style                                 | 56 Frame               |
| Cylinder Diameter (in.)                     | 2-1/2                  |
| Cylinder Length (in.)                       | 18                     |
| Chute Reach (in.)                           | 14                     |
| Rigid Casters Quantity/Diameter/Width (in.) | (2) 8 x 2              |
| Swivel Caster Quantity/Diameter/Width       | (2) 6 x 2              |
| Accepted Drum Diameter (in.)                | 16.5 to 23.5           |
| Accepted Drum Height (in.)                  | 27.5 to 39.5           |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=766>