# Steel Lift Master Boom 24 In. Fixed 15 Degrees 4,000 Lb. Capacity Blue and Yellow

**MODEL LM-F15-4-24**

Fork Truck Attachments / Lift Master Fork Truck Booms



## PRODUCT OVERVIEW

The lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

## KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**372 lbs** | ASSEMBLED SIZE<br>**32" W x 87" L x 33" H** | SHIP WEIGHT<br>**376 lbs** |
| PACKAGE 1 SIZE<br>**32" W x 87" D x 33" H** | COLOR / FINISH<br>**Blue (Base Frame)/Yellow (Extension)** | FREIGHT TYPE<br>**LTL Loose** |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS






## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 4,000 |
| **Fork Pocket Center (in.)** | 24 |
| **Fork Pocket Width/Height (in.)** | 7-1/2 x 2-1/2 |
| **Restraint Length (in.)** | 36 |
| **Boom Style** | Telescoping |
| **Minimum/Maximum Hook Point (in.)** | 36/144 |
| **Single-Hook Capacity at 36" (lb.)** | 4000 |
| **Single-Hook Capacity at 48" (lb.)** | 3750 |
| **Single-Hook Capacity at 60" (lb.)** | 3500 |
| **Single-Hook Capacity at 72" (lb.)** | 3250 |
| **Single-Hook Capacity at 84" (lb.)** | 3000 |
| **Single-Hook Capacity at 96" (lbs.)** | 2750 |
| **Single-Hook Capacity at 108" (lbs.)** | 2500 |
| **Single-Hook Capacity at 120" (lbs.)** | 2250 |
| **Single-Hook Capacity at 132" (lbs.)** | 2000 |
| **Single-Hook Capacity at 144" (lbs.)** | 1750 |
| **Overall Extended Height (in.)** | 48-1/2 |
| **Retracted Hook Height (in.)** | 12-13/16 |
| **Extended Hook Height (in.)** | 28-11/32 |
| **Overall Extended Length (in.)** | 147 |
| **Retracted Height (in.)** | 33 |
| **Retracted Length (in.)** | 87 |
| **Overall Width (in.)** | 33 |
| **Retracted center of Gravity (in.)** | 34-7/8 |
| **Extended Center of Gravity (in.)** | 50-7/8 |
| **Horizontal Center of Gravity (in.)** | 16 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=473