Laminated Rubber Wheel Chock with Rubber Grip Handle 10-1/8 In. x 12-3/8 In. x 5-1/2 In. Black

MODEL LWC-14M

Loading Dock Equipment / Rubber Wheel Chocks



PRODUCT OVERVIEW

The rubber Wheel Chock is constructed of reinforced rubber to provide a sure grip on virtually any surface. The curved surface contours to fit tires. Rubber resists tearing, abrasion, ozone weathering, etc. The functional design is durable in all weather conditions.

KEY FEATURES

- Reinforced rubber resists tearing, abrasion and ozone weathering
- Functional design is durable in all weather conditions
- Rubber provides a sure grip on virtually any surface
- Curved surface contours to fit any tire style


CORE PRODUCT DATA

ASSEMBLED WEIGHT **12 lbs**	ASSEMBLED SIZE **12.375" W x 10.125" L x 5.5" H**	SHIP WEIGHT **14 lbs**
PACKAGE 1 SIZE **11" W x 13" D x 8" H**	COLOR / FINISH **Black**	FREIGHT TYPE **Parcel**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS







PRODUCT SPECIFICATIONS

Wheel Chock Connection	None
Wheel Chock Usage	Multi-Purpose
Built-In Handles / Poles	Yes
Grip Surface Material	Laminated Rubber
Handle Height	1.75
Usable Chock Width (in.)	9-1/2
Bumper Type	Laminated Rubber with Rubber Grips

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **30 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=79