Steel Economy Stabilizing Jack with Hard Rubber Wheels 18-1/4 In. x 16-5/8 In. x 41 In. 50,000 Lb. Static Capacity Yellow

MODEL SJ-35-EF

Loading Dock Equipment / Trailer Stabilizing Jacks



PRODUCT OVERVIEW

Trailer stabilizing jacks are used to prevent up-ending of semi-trailers when they are not connected to a tractor during loading and unloading operations. Throughout the loading and unloading process it is always recommended to use two jacks, one on each side of the front of the trailer. The trailer must be situated on a flat, stable and improved (preferably concrete) surface, while the jack sits perpendicular to the underside of the trailer. Every jack is built of a high strength steel construction with a flush-type Zerk fitting for lubricating ACME screw. A yellow powder coat finish and a reflective collar for visibility at night are both included. Each jack meets OSHA regulations when used with wheel chocks. **The color of handles included with...

KEY FEATURES

- Square top plate
- Reflective collar increases visibility at night
- Manual raising and lowering mechanism
- Meets OSHA regulations when used with wheel chocks

CORE PRODUCT DATA


ASSEMBLED WEIGHT **57 lbs**	ASSEMBLED SIZE **16.625" W x 18.25" L x 41" H**	SHIP WEIGHT **57 lbs**
PACKAGE 1 SIZE **18" W x 42" D x 18" H**	COLOR / FINISH **Yellow**	FREIGHT TYPE **Parcel**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS







PRODUCT SPECIFICATIONS

Uniform Static Capacity (lb.)	50,000
Uniform Lifting Capacity (lb.)	5,000
Lowered Height (in.)	41
Raised Height (in.)	57-1/2
Wheel Size (in.)	8
Wheel Type	Hard Rubber
Base Type	Economical
Handles (qty.)	4
Top Plate Width/Length (in.)	5 x 5
Swivel Head Maximum Extension Distance (in.)	7-5/16
Swivel Head Screw Diameter (in.)	1-1/2
ACME Threads OD (in.)	1-1/2
ACME Threads Per Inch	8
Overall Width (in.)	16-5/8
Overall Depth (in.)	18-1/4

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=90