Shutter Mounted Exhaust Fan 24 In. Blade Diameter Silver

MODEL SME-24

Facilities Maintenance / Shutter Mounted Exhaust Fans



PRODUCT OVERVIEW

The shutter mounted exhaust fan offers inside-building installation only with vents outside. Eliminate need for external framing and shutter. Ideally suited for thin wall buildings. This fan is totally enclosed and permanently lubricated. Pull chain switch. No cord. Junction box provided for direct wiring. Meets OSHA standards.

KEY FEATURES

- Shutter mounted exhaust fan eliminates the need for external framing and shutter
- Includes a 1/4 Horsepower motor with 115 voltage 1 phase 1.1 Amps power supply
- Fan is completely enclosed and permanently lubricated for maximum efficiency
- Includes a junction box for direct wiring in order to meet OSHA 1910 212(a)(5) standards

CORE PRODUCT DATA

ASSEMBLED WEIGHT **39 lbs**	ASSEMBLED SIZE **28" W x 13" L x 28" H**	SHIP WEIGHT **41 lbs**
PACKAGE 1 SIZE **28" W x 28" D x 13" H**	COLOR / FINISH **Silver**	FREIGHT TYPE **Parcel**

AVAILABILITY Quote Required - Please Contact Sales **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Blade Diameter (in.)	24
Motor Horsepower	1/4
Amps High	2.5
CFM High	3400
CFM Low	2770
Voltage/Phase	115V/1PH
OSHA	1910.212(a)(5)

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Johnson City, TN 37615**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

See the live product page for current documents and downloads.

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=121