Steel Semi-Automatic Stretch Wrap Machine 50 In. Turntable Diameter 4,000 Lb. Capacity Blue / Yellow

MODEL SWA-50

Packaging Equipment / Powered Stretch Wrap Machines



PRODUCT OVERVIEW

The semi-automatic stretch wrap machine design offers bigger carousel sizes with carousel rotation that is controlled by a foot switch. The power input has variable AC motor that allows adjustable deck speed and includes soft-start/stop. The film-wrap tension is controlled with an adjustable, friction-brake assembly. Film placement is controlled manually by moving the carriage assembly up and down on the vertical mast. An easy-to-release, hand operated carriage-brake allows the carriage to move freely making film application fast and simple. The system will accept 10 (in.) to 20 (in.) material. The unit ships with mast disconnected-simply raise mast and clamp into place.

KEY FEATURES

- Stretch wrap design increases shipping productivity
- Simple depress foot pedal powers turntable
- Manual mast allows user to wrap the needed areas
- Steel construction provides a long lasting rugged use

CORE PRODUCT DATA


ASSEMBLED WEIGHT **544 lbs**	ASSEMBLED SIZE **50" W x 87.125" L x 92.375" H**	SHIP WEIGHT **615 lbs**
PACKAGE 1 SIZE **64" W x 96" D x 26" H**	COLOR / FINISH **Yellow (Deck), Blue (Frame)**	FREIGHT TYPE **LTL Palletized**


AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS







PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Turntable Diameter (in.)	50
Wrap Height (in.)	82
Turntable Height (in.)	2-1/16
Maximum Load Diameter (in.)	64
Voltage/Phase	115/1
Motor Amperage	1.8
R.P.M Variables	3-12
Motor Horsepower	1/2
Foot Switch Cord Length (in.)	96
Minimum Compatible Stretch Wrap Core ID (in.)	3
Maximum Compatible Stretch Wrap OD (in.)	11

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=367