# Steel Tilt Master Straddle DC Powered 12 Volt 2,000 Lb. Capacity Blue

**MODEL TMS-20-DC**

Ergonomic Solutions / Tilt Master & Tilt Master Straddle



## PRODUCT OVERVIEW

The tilt master straddle lifts and positions filled tote boxes or baskets without the need of a fork truck or lift table using the newly designed heavy-duty tilt master. The tilter will function as transporters by moving completed products from work station to work station without waiting for a fork truck. This lift has a thin profile to allow the user to get as close to the load as possible. It also has a standard floor lock and rolls easily on the phenolic steering wheels. Lift is designed to be used with virtually any kind of container or pallet. The unit is powered by a DC electric motor that includes an on-board battery charger and battery charge indicator.

## KEY FEATURES

- Folding ergonomic handle
- Two rigid and two swivel casters provide smooth and efficient mobility
- 90 Degrees tilt angle allows for better ergonomic access
- Push button hand control for quick lifting and lowering

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**915 lbs** | ASSEMBLED SIZE<br>**57.25" W x 73.25" L x 29" H** | SHIP WEIGHT<br>**922 lbs** |
| PACKAGE 1 SIZE<br>**64" W x 64" D x 36" H** | COLOR / FINISH<br>**Blue** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS






## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 2,000 |
| **Adjustable Fork Spacing (in.)** | 1/2 to 28-1/2 |
| **Straddle (in.)** | 49-5/16 |
| **Operator Reach (in.)** | 12-1/2 |
| **Fork Width (in.)** | 4 |
| **Fork Length (in.)** | 36 |
| **Fully Rotated Fork Height (in.)** | 72-1/8 |
| **Lowered Fork Height (in.)** | 3 |
| **Maximum Tilt Degree** | 90 |
| **Power** | 12V DC |
| **Wheel Diameter (in.)** | 8 |
| **Wheel Width (in.)** | 3 |
| **Wheel Type** | Phenolic |
| **Folding Handle Length (in.)** | 20 |
| **Load Center (in.)** | 18 |
| **Level Height (in.)** | 29 |
| **Fully Rotated Mast Height (in.)** | 37 |
| **Battery Depth** | 11 |
| **Battery Width** | 7 |
| **Battery Height** | 9 |
| **Battery Weight** | 42 |
| **Battery Freight Class** | 70 |
| **Battery NMFC Number** | 60680 |
| **Battery NMFC Description** | UN2794 BATTERIES WET FILLED WITH ACID |
| **Battery Subclass** | 1 |
| **Lithium Battery Configuration** | C -- Contained In |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=221