

# Stainless Steel Manual Load Stacker 220 Lb. Capacity Silver

**MODEL ULM-MS-220**

Stainless Steel Bronze / Stainless Steel Manual Load Stacker

## PRODUCT OVERVIEW

The 304L Stainless Steel manual load stacker is a great way to transport products in sanitary settings. The compact 304L stainless steel design including hydraulic cylinders and piston not only helps transport heavy loads around the work area, but also fits in a compact area for space saving when not in use. Due to the cradle design, goods can be placed on the stacker from three sides without the need to change the placement of the stacker. Rolling casters are attached to provide a smooth transfer of products, while the braking system maintains safety once the unit is in place.

## KEY FEATURES

- Stainless steel construction for use in sterilized environments
- Open design for simple washing and drying after use
- Manual raising and lowering unit for precise positioning
- Ergonomically formed to diminish bending and twisting

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**132 lbs**

ASSEMBLED SIZE  
**23" W x 44.0625" L x 78.5" H**

SHIP WEIGHT  
**168 lbs**

PACKAGE 1 SIZE  
**40" W x 48" D x 84" H**

COLOR / FINISH  
**Silver**

FREIGHT TYPE  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                       |                                       |
|---------------------------------------|---------------------------------------|
| Uniform Capacity (lbs.)               | 200                                   |
| Service Range (in.)                   | 5-1/2 to 61                           |
| Maximum Roll Diameter (in.)           | 24                                    |
| Load Center Distance (in.)            | 17-3/4                                |
| Load Wheel Axle to Fork Face (in.)    | 26-1/3                                |
| Turning Radius (in.)                  | 44-1/2                                |
| Leg Spacing (in.)                     | 23                                    |
| Rear Wheel Qty./Diameter/Width (in.)  | (2) 4.8 x 1.25                        |
| Front Wheel Qty./Diameter/Width (in.) | (2) 3.15 x 1.25                       |
| Wheel Material                        | Thermoplastic Rubber on Polypropylene |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=259>