# Steel Premium Truck Scissor Dock Lift 7 Ft x 8 Ft 5,000 Lb. Capacity Brown/Yellow

**MODEL WL-100-5-78**

Loading Dock Equipment / Premium Truck Scissor Dock Lifts



## PRODUCT OVERVIEW

Save time and reduce man-hours where there are no docks with a truck scissor dock lift. Engineered and designed for maximum safety and efficiency. The diamond plate deck is made of heavy gauge steel for years of use. Hydraulic cylinders feature safety velocity fuse if line breaks. It comes complete with upper travel limit switch and overload relief valve. The push-button control is on a long coil cord. Pre-wired control box includes magnetic starter and overload fuse. High visibility safety yellow removable handrails with fixed toe boards are standard. Includes beveled toe-guards and electric toe-guards around perimeter of platform. The external motor can be located up to eight (8) feet away from lift.

## KEY FEATURES

- Unique design services semi-trailers when loading dock is unavailable
- Tread plate surface provides a safe non-slip grip
- Safety velocity fuses protect the hydraulic cylinders
- Upper travel limit switch cuts power to unit when max raised height is reached

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**3059 lbs** | ASSEMBLED SIZE<br>**84" W x 114" L x 53" H** | SHIP WEIGHT<br>**3549 lbs** |
| PACKAGE 1 SIZE<br>**85" W x 98" D x 50" H** | COLOR / FINISH<br>**Brown / Yellow** | FREIGHT TYPE<br>**Flatbed Required** |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS









## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 5,000 |
| **Overall Frame Width (in.)** | 62 |
| **Overall Frame Length (in.)** | 93 |
| **Platform Length (in.)** | 96 |
| **Platform Width (in.)** | 84 |
| **Lowered Height (in.)** | 8 |
| **Raised Height (in.)** | 68 |
| **Push Button Coil Cord Length (ft.)** | 4-20 |
| **External Motor Horsepower** | 6.5 |
| **External Motor Voltage/Phase** | 460/3 |
| **Motor Hertz** | 60 |
| **Motor Weight (lb.)** | 300 |
| **Axle Side Load Capacity (lb.)** | 3,000 |
| **Axle End Load Capacity (lb.)** | 3,750 |
| **Handrail Height (in.)** | 45 |
| **Handrail Midrail Height (in.)** | 21 |
| **Toeboard Height (in.)** | 4 |
| **Beveled Toe Guard (in.)** | 5 |
| **Platform Type** | Treadplate |
| **Platform Thickness (in.)** | 1/4 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=1