

Steel Work Platform With Poly Casters, 2 Door Entry, and 84 In. Expanded Back 48 In. x 48 In. 1,000 Lb. Capacity Blue

MODEL WP-4848-CA-84B-DD

Fork Truck Attachments / Work Platforms

PRODUCT OVERVIEW

This convenient fork truck work platform quickly and safely raises maintenance personnel where they are needed. Attaches to fork truck by inserting forks into fork pockets and securing platform to fork truck. Fork locks secure platform to forks. Expanded metal backing on fourth side. Includes checker floor plate platform and long strap with hook to attach platform to fork truck. A maximum of two (2) people can be in the work platform at one time. Meets California OSHA specifications.

KEY FEATURES

- Handrails on three sides ensures worker safety
- Included casters for easy movement between areas
- Extended back for increased safety
- Dual doors for access from either side

CORE PRODUCT DATA

ASSEMBLED WEIGHT
213 lbs

ASSEMBLED SIZE
48" W x 51" L x 93.625" H

SHIP WEIGHT
213 lbs

PACKAGE 1 SIZE
48" W x 50" D x 57" H

COLOR / FINISH
Blue / Yellow

FREIGHT TYPE
LTL Loose

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1,000
Fork Pocket Center (in.)	24
Front and Rear Fork Pocket Width (in.)	7-3/4
Rear Fork Pocket Height (in.)	3-7/8
Front Fork Pocket Height (in.)	1-7/8
Strap Length (in.)	36
Top Rail Height (in.)	42
Mid Rail Height (in.)	21
Entry Style	Dual Side Door
Toeboard Height (in.)	4-1/8
Handrail Design	Fixed
Door Width (in.)	16
High Back Height (in.)	84
Platform Size (in.)	48 x 48
Caster Quantity/Diameter/Width (in.)	(4) 4x1-1/4
Caster Quantity Type	(2) Swivel (2) Swivel with Brake
Caster Material	Poly on Poly
Anchor Point Capacity (lbs.)	350

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=470>